

USA Edition

Official Installation Competition Manual 2024

3. EMMA rules – Installation Quality

The installation quality judging criteria are formulated to promote system durability and longevity, as well as logical integration and visual impression.

The installation quality judging will be performed according to this official rulebook by one or two installation judges (depending on category). These judges are specially qualified and trained to work with the rulebook to determine the installation quality.

After the installation quality judging, the competitor will receive a qualified and objective feedback about the quality of the installed audio system in regards to the criteria outlined within this rulebook.

EMMA installation has been broken down into sections that can be judged and evaluated within an understandable level of classification. The judges will not tell you "your car has a good or a bad installation or what points you have earned". Together with their qualified judgement and the help of the score sheet they will explain exactly the quality of the installation in all relevant details. The awarded score will be easy to follow for the competitor, if necessary, with support from the EMMA Rulebook. Furthermore, the competitor can learn the potential of their own system installation. The judges are allowed to give the contestants tips and hints on how to improve the installation of their audio system (without using brand names). This will allow the competitor, a qualified dealer or experienced colleagues in a competition team to help improve the installation and potential use of equipment.

Installation rules for: SQ E - Category

To be judged	Content	Points
Presentation to the public	Show off the vehicle & installation to the public during the event time Allow spectators to listen to the system	10

	Will be checked several times a day	
Cleanliness	 Vehicle exterior should be "car-wash-clean", interior should be vacuumed (not perfect but reasonably clean) Car Wash clean y/n Passenger compartment vacuumed y/n Dedicated components of the system installed in the engine compartment & trunk clean y/n 	6
System/Wiring Diagram present	(deduct 2 points per not cleaned area)	
Main fuse present y/n	2 points for each Diagram if present Check, if a main fuse is installed into the main power wire within 40cm from any positive battery post and/or before passing any metal panel. Power diagram is necessary for judging. (if no, 0 points will be awarded)	4 10
Are all components securely mounted?	 Check all components by physical inspection if fixed y/n Head Unit Other devices Amplifiers Speakers (if n/a, points will be awarded, deduct 2 points per not fixed 	24
Protection of Speakers	component, minimum 0) A speaker which is not installed completely under the window line (outer frame diameter of speaker) does not need protection speaker protection shall be defined as not flexible.	5
	Check whether the affected speakers in the interior compartment's front doors and in the foot-room are protected from physical damage. Hidden speakers like mounted under the dashboard do not need a protection when they cannot be reached with the foot of driver or passenger. One should not be able to touch the membrane with a cylindrical object with a diameter of 3 cm. There should be at least one protective element per speaker.	
	(Deduct 2 points for any speaker not protected, minimum 0). All other speakers do not need protection	
First Optic impression	 Check all components if they create the impression of "a finished installation" or "under construction" Head Unit Other devices Amplifiers Speakers / Speaker enclosures 	10
	(if n/a, points will be awarded, deduct 1 point per "under construction" component, minimum 0)	
	Total Points	69

Installation rules for: SQ S – Category

To be judged	Content				Point
Presentation to the public	Allow specta System diag	e vehicle & installat ators to listen to th ram on display for ked several times a	e system spectators	olic during the event time	
Cleanliness	vacuumed (Car W Passe Dedic comp	rior should be "car not perfect but rea 'ash clean y/n nger compartment ated components c artment & trunk cle pints per not cleane	sonably clean vacuumed y/ of the system i ean y/n)	
System/Wiring Diagram present	2 points for	each Diagram if pr	esent		
Main fuse present y/n	from any po Power diagr		and/or before r judging.	n power wire within 40cm e passing any metal panel.	:
Are all the wires to the components fused?	the audio/m three minut • Head	ulti-media system es (for all in total, r Unit devices	. All these fuse	<pre>/ component belonging to es must be visible within utes for every fuse!!!)</pre>	:
	(if n/a or no minimum 0)	•	points per not	fused component,	
	EMMA Back components	s, wire diameters a in case that no wiri	ut a form at th s well as fuses	e registration where all should be filled in by the prepared and available	
Is the fuse value appropriate to the wire size?	for the wire	it is protecting (ac	cording to the	tem is of appropriate size VW75212 - ngen im Kraftfahrzeug):	:
	Fuse	Size Matrix			
		Cable size	AWG	Fuse Rating	
		0,5mm ²	20	10 Ampere	
		1,0mm²	17	15 Ampere	
		1 Emm ²	15	20 Amporo	

15

20 Ampere

1,5mm²

		_,			
		4,0mm²	11	30 Ampere	
		6,0mm²	9	50 Ampere	
		10mm²	7	60 Ampere	
		16mm²	5	100 Ampere	
		25mm²	4	125 Ampere	
		35mm²	2	175 Ampere	
		50mm²	0	250 Ampere	
		70mm²	2/0	300 Ampere	
	formulas in documente Voltage use This rule ap power distr pay close a distribution sides of a s combined o (if n/a, wro fuse, minim	the judge book. In t ed and handed out to ed for calculation is U oplies to all electrical ribution blocks, bush ttention to all batter o block. There can be hort circuit and the o current of all sources ng size or not visible num 0)	his case, the o the judges f J=12V conductors bars etc. On n ries / fuses fe power sourc conductor must feeding the c, deduct 2 pc	in the power system, nultiple battery systems eding current to any ces connected on both ust withstand the short circuit.	
Any interior wires visible?	seating pos	iv wire of the system ition with the doors oints for any visible	closed and o		5
	that goes w	ith the device to the first the device to the first the operated at	e connector o	e connected by the cable of the HU/Car and the it, no attention will be	
			•	ystem (change track would (visible connector is ok)!	
	because it s	streams.		as not to be installed -	
Are all components securely mounted?	HeadOthe	omponents by physic l Unit r devices lifiers kers	cal inspectior	n if fixed y/n	24
	(if n/a, poir	nts will be awarded,	deduct 2 poi	nts per not fixed	

2,5mm²

13

20 Ampere

Protection of Speakers	A speaker which is not installed completely under the window line (outer frame diameter of speaker) does not need protection. Speaker protection shall be defined as not flexible.	5
	Check whether the affected speakers in the interior compartment's front doors and in the foot-room are protected from physical damage. Hidden Speakers like mounted under the dashboard do not need a protection when they cannot be reached with the foot of driver or passenger. One should not be able to touch the membrane with a cylindrical object with a diameter of 3 cm. There should be at least one protective element per speaker.	
	(Deduct 2 points for any speaker not protected, minimum 0). All other speakers do not need protection	
Does the vehicle allow a normal use?	EMMA is allowing modifications to the vehicle's interior (except in OEM) to install audio components.	6
	The driver/ passenger should sit comfortably and be able to operate the controls of the car without obstruction (look for sub/speakers up front or too high raised floor).	
	As the OEM has given the most safety and comfort in the limited space of the passenger cabin, EMMA will use the OEM surfaces as references.	
	The passenger foot room must not be smaller than the OEM foot room on the driver side between seat and pedals.	
	Judging will be done in the regular driving position of the vehicles operator.	
First Optic impression	 Check all components if they create the impression of "a finished installation" or "under construction" Head Unit Other devices Amplifiers Speakers / Speaker enclosures 	10
	(if n/a, points will be awarded, deduct 1 point per "under construction" component, minimum 0)	

Total Points 115

Installation rules fo	r: SQ M – Category and Multimedia	
To be judged	Content	Points
Presentation to the public	Show off the vehicle & installation to the public during the event time Allow spectators to listen to the system System diagram on display for spectators	10

	Exception: at the event active judges / back office staff's cars can remain closed due to safety reason	
	Will be checked several times a day	
Bonus Presentation to the public	Some activity by the competitor to promote their car / installation / presentation during a dedicated period of time	5
Cleanliness	 Vehicle exterior should be "car-wash-clean", interior should be vacuumed (not perfect but reasonably clean) Car Wash clean y/n Passenger compartment vacuumed y/n Dedicated components of the system installed in the engine compartment & trunk clean y/n 	6
	(deduct 2 points per not cleaned area)	
System documentation	 Check for: Signal flow-chart Wire/Fuse Diagram Documentation (photo-log) of not accessible connections / components 	10
	(deduct 1 point per missing element, minimum 0)	
Explanation of system to the judges	Up to 7 minute explanation of the system to the judges by owner of vehicle / dedicated presenter (no movie)	5
	Hint: Focus on how and why the installation was built, not on brands or the final result.	
Main fuse present y/n	2 points will be deducted per 30sec. Over time Check, if a main fuse is installed into the main power wire within 40cm from any positive battery post and/or before passing any metal panel. Power diagram is necessary for judging.	10
	(if no, 0 points will be awarded)	
Are all the wires to the components fused?	 Check if a fuse is installed in the wire for any component belonging to the audio/multi-media system. All these fuses must be visible within three minutes (for all in total, not three minutes for every fuse!!!) Head Unit Other devices Amplifiers 	15
	(if n/a or not visible, deduct 2 points per not fused component, minimum 0)	
	Power diagram is necessary for judging. EMMA Back Office will hand out a form at the registration where all components, wire diameters as well as fuses should be filled in by the	
	7	

competitor in case that no wiring diagram is prepared and available for the judging process

Is the fuse value appropriate to the wire size? Check, if any fuse belonging to the audio system is of appropriate size for the wire it is protecting (according to the VW75212 -Dimensionierung von Leitungen und Sicherungen im Kraftfahrzeug):

Fuse	Size Matrix		
	Cable size	AWG	Fuse Rating
	0,5mm²	20	10 Ampere
	1,0mm²	17	15 Ampere
	1,5mm²	15	20 Ampere
	2,5mm²	13	20 Ampere
	4,0mm²	11	30 Ampere
	6,0mm²	9	50 Ampere
	10mm²	7	60 Ampere
	16mm²	5	100 Ampere
	25mm²	4	125 Ampere
	35mm²	2	175 Ampere
	50mm²	0	250 Ampere
	70mm²	2/0	300 Ampere

Alternatively, wire sizes and fuse rates can be calculated with the formulas in the judge book. In this case, the calculations must be documented and handed out to the judges for checking. Voltage used for calculation is U=12V

This rule applies to all electrical conductors in the power system, power distribution blocks, busbars etc. On multiple battery systems pay close attention to all batteries / fuses feeding current to any distribution block. There can be power sources connected on both sides of a short circuit and the conductor must withstand the combined current of all sources feeding the short circuit.

(if n/a, wrong size or not visible, deduct 2 points per not appropriate fuse, minimum 0)

Any interiorCheck, if any wire of the system installation is visible from the driver'swires visible?seating position with the doors closed and open.

(deduct 2 points for any visible system wire, minimum 0)

Mobile devices such as smartphones that are connected by the cable that goes with the device to the connector of the HU/Car and the device itself will be operated at the head unit, no attention will be paid to this cable.

If the mobile device is used to operate the system (change track would be enough), there should be no wire visible (visible connector is ok)!

Hint: this could also mean that the device must not be installed - because it streams.

5

20

Wires properly terminated?	Check, if all wires are properly terminated - either by physical inspection or by photo log	5
	(deduct 2 points per wire not properly terminated wire, minimum 0)	
Wire terminations protected y/n	Check, if wire terminations are installed in such a way that short circuits are avoided / covered by a non-conductive material in vehicles driving condition (all panels/covers on etc.) and appropriate measures are taken if expressed to moisture (e.g. in the doors) - either by physical inspection or by photo log	10
	(deduct 1 point per wire that's not properly terminated, minimum 0)	
Wires protected from damage y/n	Wires that pass metal (e.g. from engine compartment to interior) should be protected by grommets, rubbers or similar	5
	For wires that are mechanically stressed (e.g. into the door) or that are close to moving parts (e.g. engine-belts) protective sleeving should be used if not installed to OEM cable trays.	
	(deduct 2 points per not properly protected wire, minimum 0)	
Are all components securely mounted?	 Check all components by physical inspection if fixed y/n Head Unit Other devices Amplifiers Speakers 	24
	(if n/a, points will be awarded, deduct 2 points per not fixed component, minimum 0)	
Protection of Speakers	A speaker which is not installed completely under the window line (outer frame diameter of speaker) does not need protection Speaker protection shall be defined as not flexible.	5
	Check whether the affected speakers in the interior compartment's front doors and in the foot-room are protected from physical damage. Hidden Speakers like mounted under the dashboard do not need a protection when they cannot be reached with the foot of driver or passenger. One should not be able to touch the membrane with a cylindrical object with a diameter of 3 cm. There should be at least one protective element per speaker.	
Does the vehicle allow a normal use?	(Deduct 2 points for any speaker not protected, minimum 0). All other speakers do not need protection EMMA is allowing modifications to the vehicle's interior (except in OEM) to install audio components.	6
	The driver/ passenger should sit comfortably and be able to operate the controls of the car without obstruction (look for sub/speakers up front or too high raised floor).	

	As the OEM has given the most safety and comfort in the limited space of the passenger cabin, EMMA will use the OEM surfaces as references.	
	The passenger foot room must not be smaller than the OEM foot room on the driver side between seat and pedals.	
	Judging will be done in the regular driving position of the vehicles operator.	
First Optic impression	 Check all components if they create the impression of "a finished installation" or "under construction" Head Unit Other devices Amplifiers Speakers / Speaker enclosures (if n/a, points will be awarded, deduct 1 point per "under construction" component, minimum 0)	10
Craftsmanship	Check wire-routing, terminations, installation of components, installation of panels, surface finishes, equal gaps, etc. for the categories: Wiring Head Unit Amplifiers Speakers Other components	10
	(deduct 2 points per element where no effort was taken (to modify it from OEM state), deduct 1 point per element where poor effort was taken, minimum 0 => note on the score sheet for what points are deducted)	
	Total Points	161

Installation rules for: SQ X Limited - Category

To be judged	Content	Points
Presentation to the public	Show off the vehicle & installation to the public during the event time Allow spectators to listen to the system System diagram on display for spectators	10
	Exception: at the event active judges / back office staff's cars can remain closed due to safety reason	
	Will be checked several times a day	
Bonus Presentation to the public	Some activity by the competitor to promote their car / installation / presentation during a dedicated period of time	5

Cleanliness	 Vehicle exterior should be "car-wash-clean", interior should be vacuumed (not perfect but reasonably clean) Car Wash clean y/n Passenger compartment vacuumed y/n Dedicated components of the system installed in the engine compartment & trunk clean y/n 	6
	(deduct 2 points per not cleaned area)	
System documentation	 Check for: Signal flow-chart Wire/Fuse Diagram Documentation (photo-log) of not accessible connections / components 	10
	(deduct 1 point per missing element, minimum 0)	
Explanation of system to the judges	Up to 7 minute explanation of the system to the judges by owner of vehicle / dedicated presenter (no movie)	10
	Hint: Focus on how and why the installation was built, not on brands or the final result.	
	1 point will be deducted per 30sec. Over time	
Main fuse present y/n	Check, if a main fuse is installed into the main power wire within 40cm from any positive battery post and/or before passing any metal panel. Power diagram is necessary for judging.	10
	(if no, 0 points will be awarded)	
Are all the wires to the components fused?	 Check, if a fuse is installed in the wire for any component belonging to the audio/multi-media system. All these fuses must be visible within three minutes (for all in total, not three minutes for every fuse!!!) Head Unit Other devices Amplifiers 	15
	(if n/a or not visible, deduct 2 points per not fused component, minimum 0)	
	Power diagram is necessary for judging. EMMA Back Office will hand out a form at the registration where all components, wire diameters as well as fuses should be filled in by the competitor in case that no wiring diagram is prepared and available for the judging process	
Is the fuse value appropriate to the wire size?	Check, if any fuse belonging to the audio system is of appropriate size for the wire it is protecting (according to the VW75212 - Dimensionierung von Leitungen und Sicherungen im Kraftfahrzeug):	20

Fuse Size Matrix				
Cable size	AWG	Fuse Rating		
0,5mm ²	20	10 Ampere		
1,0mm ²	17	15 Ampere		
1,5mm²	15	20 Ampere		
2,5mm ²	13	20 Ampere		
4,0mm ²	11	30 Ampere		
6,0mm ²	9	50 Ampere		
10mm ²	7	60 Ampere		
16mm ²	5	100 Ampere		
25mm ²	4	125 Ampere		
35mm ²	2	175 Ampere		
50mm ²	0	250 Ampere		
70mm ²	2/0	300 Ampere		

Alternatively, wire sizes and fuse rates can be calculated with the formulas in the judge book. In this case, the calculations must be documented and handed out to the judges for checking. Voltage used for calculation is U=12V

This rule applies to all electrical conductors in the power system, power distribution blocks, busbars etc. On multiple battery systems pay close attention to all batteries / fuses feeding current to any distribution block. There can be power sources connected on both sides of a short circuit and the conductor must withstand the combined current of all sources feeding the short circuit.

(if n/a, wrong size or not visible, deduct 2 points per not appropriate fuse, minimum 0)

5

5

Any interiorCheck, if any wire of the system installation is visible from the driver'swires visible?seating position with the doors closed and open.

(Deduct 2 points for any visible system wire, minimum 0)

Mobile devices such as smartphones that are connected by the cable that goes with the device to the connector of the HU/Car and the device itself will be operated at the head unit, no attention will be paid to this cable.

If the mobile device is used to operate the system (change track would be enough), there should be no wire visible (visible connector is ok)!

Hint: this could also mean that the device must not be installed - because it streams.

Wires properlyCheck, if all wires are properly terminated - either by physicalterminated?inspection or by photo log

(deduct 2 points per not properly terminated wire, minimum 0)

Wire terminations protected y/n	Check, if wire terminations are installed in such a way that short circuits are avoided / covered by a non-conductive material in vehicles driving condition (all panels/covers on etc.) and appropriate measures are taken if expressed to moisture (e.g. in the doors) - either by physical inspection or by photo log	10
	(deduct 1 point per not properly protected wire termination, minimum 0)	
Wires protected from damage y/n	Wires that pass metal (e.g. from engine compartment to interior) should be protected by grommets, rubbers or similar	5
	For wires that are mechanically stressed (e.g. into the door) or that are close to moving parts (e.g. engine-belts) protective sleeving should be used if not installed to OEM cable trays.	
	(deduct 2 points per not properly protected wire, minimum 0)	
Are all components securely mounted?	 Check all components by physical inspection if fixed y/n Head Unit Other devices Amplifiers Speakers 	24
	(if n/a, points will be awarded, deduct 2 points per not fixed component, minimum 0)	
Protection of Speakers	A speaker which is not installed completely under the window line (outer frame diameter of speaker) does not need protection. Speaker protection shall be defined as not flexible.	5
	Check whether the affected speakers in the interior compartment's front doors and in the foot-room are protected from physical damage. Hidden Speakers like mounted under the dashboard do not need a protection when they cannot be reached with the foot of driver or passenger. One should not be able to touch the membrane with a cylindrical object with a diameter of 3 cm. There should be at least one protective element per speaker.	
	(Deduct 2 points for any speaker not protected, minimum 0). All other speakers do not need protection	
Does the vehicle allow a normal use?	EMMA is allowing modifications to the vehicle's interior (except in OEM) to install audio components.	6
	The driver/ passenger should sit comfortably and be able to operate the controls of the car without obstruction (look for sub/speakers up front or too high raised floor).	
	As the OEM has given the most safety and comfort in the limited space of the passenger cabin, EMMA will use the OEM surfaces as references.	

	Total Points	231
	(up to 3 bonus points possible per request - 1 for the idea itself, 1 if average realization, 2 if good realization)	
	The competitor must submit their requests (max. 20) for bonus points together with their presentation	
	 system is installed, That make it a creative system presentation 	
	 Attract spectators (no noise accepted!!!), Allow normal use of the vehicle without sacrifice though a system is installed. 	
Bonus points	 Award bonus points for elements that belong to the installation and That promote components in an extraordinary way, Attract constants (no point accounted UI) 	15
Popus points	(deduct 1 point per element not following the design idea, minimum 0)	4 5
Design of trunk	components installed to the trunk follow a clear design idea y/n	5
	(deduct 1 point per element not following the design idea, minimum 0)	
Design of interior	deducted) components installed to the interior follow a clear design idea y/n	5
	(deduct 2 points per element where no effort was taken (to modify it from OEM state), deduct 1 point per element where poor effort was taken, minimum 0 => note on the score sheet for what points are	
	 Other components 	
	 Amplifiers Speakers 	
	WiringHead Unit	
	categories:	
Craftsmanship	Check wire-routing, terminations, installation of components, installation of panels, surface finishes, equal gaps, etc. for the	50
	(if n/a, points will be awarded, deduct 1 point per "under construction" component, minimum 0)	
	 Speakers / Speaker enclosures 	
	Other devicesAmplifiers	
	installation" or "under construction"Head Unit	10
First Optic impression	Check all components if they create the impression of "a finished	10
	Judging will be done in the regular driving position of the vehicles operator.	
	room on the driver side between seat and pedals.	
	The passenger foot room must not be smaller than the OEM foot	

Installation rules for: SQ X Unlimited - Category

To be judged	Content	Points
Presentation to the public	Show off the vehicle & installation to the public during the event time Allow spectators to listen to the system System diagram on display for spectators	10
	Exception: at the event active judges / back office staff's cars can remain closed due to safety reason. Will be checked several times a day	
Bonus Presentation to the public	Some activity by the competitor to promote their car / installation / presentation during a dedicated period of time	5
Cleanliness	 Vehicle exterior should be "car-wash-clean", interior should be vacuumed (not perfect but reasonably clean) Exterior clean y/n Passenger compartment clean y/n Dedicated components of the system installed in the engine compartment & trunk clean y/n 	6
System documentation	 (deduct 2 points per not cleaned area) Check for: Signal flow-chart Wire/Fuse Diagram Documentation (photo-log) of not accessible connections / components 	10
Explanation of system to the judges	(deduct 1 point per missing element, minimum 0) Up to 15 minute explanation of the system to the judges by owner of vehicle / dedicated presenter (no movie)	10
	Hint: Focus on how and why the installation was built, not on brands or the final result. 1 point will be deducted per 30sec. Over time	
Main fuse present y/n	Check, if a main fuse is installed into the main power wire within 40cm from any positive battery post and/or before passing any metal panel. Power diagram is necessary for judging. (if no, 0 points will be awarded)	10

Are all the wires to the components fused?

Check if a fuse is installed in the wire for any component belonging to 15 the audio/multi-media system. All these fuses must be visible within three minutes (for all in total, not three minutes for every fuse!!!)

- Head Unit •
- Other devices
- Amplifiers

(if n/a or not visible, deduct 2 points per not fused component, minimum 0)

Power diagram is necessary for judging.

EMMA Back Office will hand out a form at the registration where all components, wire diameters as well as fuses should be filled in by the competitor in case that no wiring diagram is prepared and available for the judging process

Check, if any fuse belonging to the audio system is of appropriate size Is the fuse value for the wire it is protecting (according to the VW75212 appropriate to the Dimensionierung von Leitungen und Sicherungen im Kraftfahrzeug): wire size?

Fuse Size Matrix				
Cable size	AWG	Fuse Rating		
0,5mm²	20	10 Ampere		
1,0mm²	17	15 Ampere		
1,5mm²	15	20 Ampere		
2,5mm ²	13	20 Ampere		
4,0mm ²	11	30 Ampere		
6,0mm ²	9	50 Ampere		
10mm ²	7	60 Ampere		
16mm ²	5	100 Ampere		
25mm ²	4	125 Ampere		
35mm ²	2	175 Ampere		
50mm ²	0	250 Ampere		
70mm ²	2/0	300 Ampere		

Alternatively, wire sizes and fuse rates can be calculated with the formulas in the judge book. In this case, the calculations must be documented and handed out to the judges for checking. Voltage used for calculation is U=12V

This rule applies to all electrical conductors in the power system, power distribution blocks, busbars etc. On multiple battery systems pay close attention to all batteries / fuses feeding current to any distribution block. There can be power sources connected on both sides of a short circuit and the conductor must withstand the combined current of all sources feeding the short circuit.

(if n/a, wrong size or not visible, deduct 2 points per not appropriate fuse, minimum 0)

Any interior wires visible?	Check, if any wire of the system installation is visible from the driver's seating position with the doors closed and open.	
	(deduct 2 points for any visible system wire, minimum 0)	
	Mobile devices such as smartphones that are connected by the cable that goes with the device to the connector of the HU/Car and the device itself will be operated at the head unit, no attention will be paid to this cable.	
	If the mobile device is used to operate the system (change track would be enough), there should be no wire visible (visible connector is ok)!	
	Hint: this could also mean that the device must not be installed - because it streams.	
Wires properly terminated?	Check, if all wires are properly terminated - either by physical inspection or by photo log	5
	(deduct 2 points per not properly terminated, minimum 0)	
Wire terminations protected y/n	Check, if wire terminations are installed in such a way that short circuits are avoided / covered by a non-conductive material in vehicles driving condition (all panels/covers on etc.) and appropriate measures are taken if expressed to moisture (e.g. in the doors) - either by physical inspection or by photo log	10
	(deduct 1 point per not properly protected wire termination, minimum 0)	
Wires protected from damage y/n	Wires that pass metal (e.g. from engine compartment to interior) should be protected by grommets, rubbers or similar	5
	For wires that are mechanically stressed (e.g. into the door) or that are close to moving parts (e.g. engine-belts) protective sleeving should be used if not installed to OEM cable trays.	
	(deduct 2 points per not properly protected wire, minimum 0)	
Are all components securely mounted?	 Check all components by physical inspection if fixed y/n Head Unit Other devices Amplifiers Speakers 	24
	(if n/a, points will be awarded, deduct 2 points per not fixed component, minimum 0)	
Protection of Speakers	Protection of speakers is not required in X Unlimited category.	

First Optic impression	 Check all components if they create the impression of "a finished installation" or "under construction" Head Unit Other devices Amplifiers Speakers / Speaker enclosures (if n/a, points will be awarded, deduct 1 point per "under construction" component, minimum 0)	10
Craftsmanship	Check wire-routing, terminations, installation of components, installation of panels, surface finishes, equal gaps, etc. for the categories: • Wiring • Head Unit • Amplifiers • Speakers • Other components (deduct 2 points per element where no effort was taken (to modify it from OEM state), deduct 1 point per element where poor effort was taken, minimum 0 => note on the score sheet for what points are deducted)	50
Design of interior	components installed to the interior follow a clear design idea y/n (deduct 1 point per element not following the design idea, minimum 0)	10
Design of trunk	components installed to the trunk follow a clear design idea y/n (deduct 1 point per element not following the design idea, minimum	10
Overall design of the vehicle	 0) To score full points, the car itself and the components installed in it must show a design theme that was followed, throughout the car; inside, outside and to the trunk compartment. It should be immediately clear that the car was designed as a project from beginning, with a clear statement to the judges and the viewers. The kind of design theme is of no matter; but the competitor should be aware that an original looking car is not able to score any points on the areas where no effort for design was taken. (deduct 1 point per element not following the design idea, minimum 0) 	10

Bonus points	Award bonus points for elements that belong to the installation and 1	.00
	 That promote components in an extraordinary way, 	
	 Attract spectators (no noise accepted!!!), 	

- Allow normal use of the vehicle without sacrifice though a system is installed,
- That make it a creative system presentation

The competitor must submit their requests (max. 50) for bonus points together with their presentation

(up to 3 bonus points possible per request - 1 for the idea itself, 1 if average realization, 2 if good realization)

Installation Matrix					
	E	S	М	Х	X Unl
Max. points	69	115	161	231	325
Presentation to the public	10	10	10	10	10
Bonus Presentation to the public			5	5	5
Cleanliness	6	6	6	6	6
System/Wiring Diagram	4	4			
System documentation			10	10	10
Explanation of system to the judges			5	10	10
Main fuse(s) present y/n	10	10	10	10	10
Are all wires to the components fused?		15	15	15	15
Is the fuse value appropriate to the wire size?		20	20	20	20
Any interior wires visible?		5	5	5	5
Wires properly terminated?			5	5	5
Wire terminations protected y/n			10	10	10
Wires protected from damage y/n			5	5	5
Are all components securely mounted?	24	24	24	24	24
Protection of speakers	5	5	5	5	
Does the vehicle allow a normal use?		6	6	6	
First Optic impression	10	10	10	10	10
Craftsmanship			10	50	50
Design of interior				5	10
Design of trunk				5	10
Overall design of vehicle					10
Bonus points				15	100

Fuse Size Matrix				
	Cable size	AWG	Fuse Rating	
	0,5mm ²	20	10 Ampere	
	1,0mm²	17	15 Ampere	
	1,5mm²	15	20 Ampere	
	2,5mm ²	13	20 Ampere	
	4,0mm ²	11	30 Ampere	
	6,0mm²	9	50 Ampere	
	10mm ²	7	60 Ampere	
	16mm ²	5	100 Ampere	
	25mm ²	4	125 Ampere	
	35mm ²	2	175 Ampere	
	50mm ²	0	250 Ampere	
	70mm ²	2/0	300 Ampere	

EMMA is powered by:



Notes:		

Official international EMMA Partners



audison















CAR MEDIA SYSTEMS























Ahead of the curve"











22

W PHOENIX GOLD

























the global car lifestyle network